



The  
Patent  
Office

The Patent Office  
Concept House  
Cardiff Road  
Newport  
South Wales  
NP9 1RH

## CERTIFIED COPY OF PRIORITY DOCUMENT

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed

*AmBrewster*


Dated

27 AUG 1997

BEST AVAILABLE COPY

**THIS PAGE BLANK (USPTO)**

For official use



9401594.8

31 JAN 94 #00287236 PAT 1 77 UC 25.00  
27 JAN 1994

Your reference

#### Notes

Please type, or write in dark ink using CAPITAL letters. A prescribed fee is payable for a request for grant of a patent. For details, please contact the Patent Office (telephone 071-438 4700).

Rule 16 of the Patents Rules 1990 is the main rule governing the completion and filing of this form.

Do not give trading styles, for example, 'Trading as XYZ company', nationality or former names, for example, 'formerly (known as) ABC Ltd' as these are not required.

#### Warning

After an application for a Patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977 and will inform the applicant if such prohibition or restriction is necessary. Applicants resident in the United Kingdom are also reminded that under Section 23, applications may not be filed abroad without written permission unless an application has been filed not less than 6 weeks previously in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction revoked.

**The  
Patent  
Office**

## Request for grant of a Patent Form 1/77

Patents Act 1977

### 1 Title of invention

1 Please give the title of the invention **Correction Tape Dispenser**

### 2 Applicant's details

#### ☐ First or only applicant

2a If you are applying as a corporate body please give:

Corporate name **The Gillette Company**

Country (and State of incorporation, if appropriate) **U.S.A.  
Delaware**

2b If you are applying as an individual or one of a partnership please give in full:

Surname

Forenames

2c In all cases, please give the following details:

Address **Prudential Tower Building,  
Boston,  
Massachusetts 02199,**

UK postcode (if applicable)

**U.S.A.**

Country  
ADP number (if known)

**771287001**

52

2d, 2e and 2f: If there are further applicants please provide details on a separate sheet of paper.

☐ **Second applicant (if any)**

2d If you are applying as a corporate body please give:

Corporate name

Country (and State  
of incorporation, if  
appropriate)

2e If you are applying as an individual or one of a partnership please give in full:

Surname

Forenames

2f **In all cases**, please give the following details:

Address

UK postcode  
(if applicable)

Country

ADP number  
(if known)

① An address for service in the United Kingdom must be supplied

Please mark correct box

① **Address for service details**

3a Have you appointed an agent to deal with your application?

Yes ☒ No ☐ → go to 3b

↓  
please give details below

Agent's name A.A. Thornton & Co.,

Agent's address Northumberland House,  
303-306 High Holborn,  
London,

Postcode WC1V 7LE

Agent's ADP number 75001

3b: If you have appointed an agent, all correspondence concerning your application will be sent to the agent's United Kingdom address.

3b If you have not appointed an agent please give a name and address in the United Kingdom to which all correspondence will be sent:

Name

Address

Postcode

ADP number  
(if known)

Daytime telephone  
number (if available)


4 Agent's or  
applicant's reference  
number (if applicable) JL

### ⑤ Claiming an earlier application date

5 Are you claiming that this application be treated as having been filed on the date of filing of an earlier application?

Yes ☐ No ☒ **→ go to 6**

**↓**  
***please give details below***

 number of earlier application or patent number

 **filing date**

(day      month      year)

☐ and the Section of the Patents Act 1977 under which you are claiming:

**Please mark correct box**

15(4) (Divisional) ☐ 8(3) ☐ 12(6) ☐ 37(4) ☐

**6** If you are declaring priority from a PCT Application please enter 'PCT' as the country and enter the country code (for example, GB) as part of the application number.

*Please give the date in all number format, for example, 31/05/90 for 31 May 1990.*

### ⑥ Declaration of priority

6 If you are declaring priority from previous application(s), please give:

Country of filing	Priority application number (if known)	Filing date (day, month, year)
Great Britain	9302589.8	10/2/93
Great Britain	9310715.9	25/5/93

- 7 The answer must be 'No' if:
- any applicant is not an inventor
  - there is an inventor who is not an applicant, or
  - any applicant is a corporate body.

8 Please supply duplicates of claim(s), abstract, description and drawing(s).

Please mark correct box(es)

- 9 You or your appointed agent (see Rule 90 of the Patents Rules 1990) must sign this request.

Please sign here ➡

A completed fee sheet should preferably accompany the fee.

## 7 Inventorship

7 Are you (the applicant or applicants) the sole inventor or the joint inventors?

Please mark correct box

Yes ☐

No ☒

A Statement of Inventorship on Patents Form 7/77 will need to be filed (see Rule 15).

## 8 Checklist

8a Please fill in the number of sheets for each of the following types of document contained in this application.

Continuation sheets for this Patents Form 1/77

-

Claim(s)

4

Description

10

Abstract

1

Drawing(s)

6

8b Which of the following documents also accompanies the application?

Priority documents (please state how many)

-

Translation(s) of Priority documents (please state how many)

-

Patents Form 7/77 – Statement of Inventorship and Right to Grant (please state how many)

1

Patents Form 9/77 – Preliminary Examination/Search

ENC

Patents Form 10/77 – Request for Substantive Examination

-

## 9 Request

I/We request the grant of a patent on the basis of this application.

Signed

A. A. Thornton & Co.

Date

27

01

94

(day

month

year)

A.A. THORNTON & CO.

Please return the completed form, attachments and duplicates where requested, together with the prescribed fee to either:


☐ The Comptroller  
The Patent Office  
Cardiff Road  
Newport  
Gwent  
NP9 1RH

or

☐ The Comptroller  
The Patent Office  
25 Southampton Buildings  
London  
WC2A 1AY

For official use

9401594.8



27 JAN 1994

Your reference

JL

**Notes**

Please type, or write in dark ink using CAPITAL letters.

No fee is required with this form.

Rule 15 of the Patents Rules 1990 is the main rule governing the completion and filing of this form.

If you do not have enough space please use a separate sheet of paper.

When an application does not declare priority at all, or declares priority from an earlier UK application, sufficient additional copies of this form must be supplied to enable the Comptroller to send one to each inventor who is not an applicant.

**The  
Patent  
Office**

**Statement of inventorship and  
of right to grant of a Patent**

**Form 7/77**

**Patents Act 1977**

**① Application details**

1a Please give the patent application number (if known):

1b Please give the full name(s) of the applicant(s):

**The Gillette Company**

**② Title of invention**

2 Please give the title of the invention:

**Correction Tape Dispenser**

**③ Derivation of right**

3 Please state how the applicant(s) derive(s) the right to be granted a patent:  
**By virtue of employment of the inventor  
by Gillette Management Inc. and agreement  
between Gillette Management Inc. and  
The Gillette Company.**

**④ Declaration**

4 I believe the person(s) named overleaf (and on any supplementary copies of this form) to be the inventor(s) of the invention for which the patent application has been made. I consent to the disclosure of the details contained in this form to each inventor named.

Please sign here ➡

Signed

*A.A. Thornton L.*

Date

27

(day

01

month

94

year)

Please turn over ➡

Please put the full name(s) and address(es) of the inventors in the boxes below:

Please underline the surnames or family names.

STEVENS, Christopher John,  
8 The Willows,  
Caversham,  
Reading,  
Berkshire, RG4 8BD,  
Great Britain.

ADP number (if known):

6490940001

on

ADP number (if known):

Please give the names of any further inventors on the back of another form 7/77 and attach it to this form.

**Reminder**

**Have you signed the declaration overleaf?**

ADP number (if known):



- 1 -

CORRECTION TAPE DISPENSER

This invention relates to a correction tape dispenser for laying down a strip or band of correction composition onto a surface, most usually paper, e.g. to cover markings thereon to facilitate the correction of a mistake.

There are known correction tape dispensers which have supply and take-up spools for the tape mounted within a case to rotate about parallel axes with the supply spool being coupled to drive the take up spool through a slipping clutch arrangement. The case may be adapted to be held directly in the hand of the user, or it may form a cartridge which is inserted into a re-usable outer housing. A length of tape extending between the spools is guided to pass out of the casing and around a tip having a relatively sharp edge which is used to press the tape against the surface onto which the correction strip is to be applied. The tape consists of a ribbon, e.g. of plastics or paper, on one side of which is carried a coating of the correction composition, this coating being on the outer side of the ribbon when it passes around the tip. In use, the device is held in the hand and the tip is pressed down onto the paper surface so that its edge presses the tape against the surface across the full width of the tape. The correction composition has an adhesive quality and has greater adhesion to the paper than its

carrier ribbon, so that when the tip is displaced across the paper surface in a direction perpendicular to the tip edge, the tip slides with respect to the ribbon causing tape to be drawn off the supply spool. The consequent rotation of the supply spool rotates the take-up spool so that a substantially constant tension is maintained in the tape and the take-up spool reels in the spent ribbon over which the tip has passed and from which the correction composition coating will have been deposited onto the paper surface. In this way a continuous strip of the correction composition is laid down onto the paper, this strip having a length according to the distance travelled by the dispenser tip.

The known correction tape dispensers operate satisfactorily as far as laying down the correction strip is concerned. However, they do require some practice to ensure that during displacement of the tip its edge is applied correctly against the paper. To a large extent the difficulty of ensuring the correct orientation of the tip is due to the device having to be held in an unnatural attitude, especially when the spools are arranged with their axes parallel to the tip edge.

The present invention addresses this drawback of the prior art devices and provides a correction tape dispenser comprising a tip having an edge for pressing the tape against a surface, a portion of tape between supply and take-up spools being guided to extend around said edge, wherein the edge is inclined to the feed direction in which the tape is guided to the tip, and the tip includes guide means on either side of the edge for redirecting the tape so that the path of the tape around the edge between the guide means is in a plane substantially perpendicular to said edge and inclined to the feed direction.

The tip employed in the dispenser of the invention allows the dispenser to be held in an orientation similar to that in which a writing instrument is normally held, namely inclined forwardly and downwardly away from the person using it, preferably at an angle to the paper in the range of  $45^{\circ}$  to  $75^{\circ}$ . As well as enabling a more natural holding position, the dispenser can allow the tip to be more readily viewed as the case enclosing the spools, and the hand of the user, can be disposed so as not to impede the user's sight of the tip. Thus, the convenience of use of the dispenser may be a substantial improvement on the prior art devices. The tape guidance can be simplified by the supply and take-up spools having their axes perpendicular to a plane containing the tip edge and substantially parallel to the feed direction.

The guide means may comprise a linear edge around which the tape extends to bend the tape path and simultaneously twist the tape. In one embodiment such linear edges are defined on respective sides of the tip by parallel ridges separated by a slot. Alternatively, the guide means on at least one side of the tip may comprise a guide element, e.g. a lateral projection, around which the tip passes to define a bend in the tape path. Conveniently, the guide element maintains the tape at the bend substantially perpendicular to the tip edge, and the tape is twisted longitudinally through substantially  $90^{\circ}$  between the guide element and the tip edge.

To retain the tape in proper cooperation with the tip edge, retention means may be provided adjacent the edge on one or both sides of the tip. The retention means can be arranged to prevent unintentional disengagement of the tape from the tip edge by defining with the tip a substantially closed eye through which the tape passes. The tip edge may have extensions to reduce risk of the tape becoming displaced over the edge extremities.

A full understanding of the invention will be gained from the following detailed description of an embodiment, reference being made to the accompanying drawings in which:

Figure 1 is a schematic view of a correction tape dispenser in accordance with the invention;

Figure 2 is a perspective view of the dispenser in use, the casing being shown cut away to reveal the tip member;

Figure 3 is a side elevation of the tip member;

Figure 4 is a side elevation of the tip member and also showing the path of the tape to and from the tip edge;

Figure 5 is a front elevation of the tip member;

Figure 6 is a perspective view illustrating the tip region of a modified embodiment of the invention, the housing having been cut away to reveal relevant details of the tape feed path;

Figure 7 is an elevation showing the internal parts of the dispenser of Figure 6;

Figures 8 and 9 are views corresponding to Figs. 6 and 7, respectively, showing a second modified correction tape dispenser according to the invention;

Figure 10 is a detailed perspective view of the tip edge portion illustrating one form of a tape retention device; and

Figures 11 to 15 are views similar to Figure 10 showing alternative devices for retaining the tape in correct cooperation with the tip edge.

The correction tape dispenser illustrated in Figures 1 to 5 of the drawings has case 1 in which are housed tape supply and take-up spools 2 and 3. The spools

are rotatable about their respective parallel axes and as well known in the art the spools are coupled by a slipping drive mechanism (not shown) whereby rotation of the supply spool 2 in response to tape 4 being drawn therefrom causes the take-up spool 3 to rotate to reel in the tape to prevent the tape becoming slack between the spools. The tape itself can be conventional having a layer of correction composition coating one side of a carrier ribbon.

The case is of generally rectangular configuration and is elongated with the spools being displaced relative to each other longitudinally of the casing. Mounted in the casing and protruding from the forward end thereof is a tip member 5, the distal end of which defines an edge 6 by means of which the tape is pressed against the paper surface for transferring a strip of correction composition from the carrier ribbon onto the paper. A length of tape extending between the supply and take-up spools is guided to pass around the tip edge 6. The guide means include posts 7, 8, 9 conveniently provided at the inner or proximal end of the tip member, and cooperating to define a first slot between posts 7 and 8 for prepositioning the tape coming from the supply spool ready for delivery in a predetermined feed direction to the tip 10, and a second slot between posts 8 and 9 for setting a fixed end position for the tape to pass away from the tip 10 in a predetermined direction parallel to the feed direction, before moving on towards the take-up spool 3. In the illustrated embodiment the feed direction is substantially parallel to the axis of the case 1, which may be desirable, but is not essential.

The tip member 5 is an integral plastics moulding and provides a tip 10 with a first portion and a second portion defining the edge 6 and at an angle to the first portion. The first portion comprises two ridges 11, 12 defining parallel rectilinear edges inclined to the

tape feed direction. A narrow slot 14 is formed between the ridges. The tape being delivered from the supply spool 2 and extending between the guide posts 7 and 8 enters this slot 14 having twisted through  $90^{\circ}$  in passing from the guide posts to the tip 10 so that the coating of correction composition faces inwardly away from the ridge 11. From the slot 14 the tape passes over the edge of ridge 11, from the inside to the outside surface thereof, and is thereby redirected to extend towards the tip edge 6 in a direction perpendicular to that edge. Having passed around the tip edge, maintaining contact with the tip surface, the tape extends perpendicularly to the edge 6 until it reaches the edge of the ridge 12 around which it then passes before undergoing a  $90^{\circ}$  twist and passing between the guide posts 8 and 10. This path of the tape is clearly depicted in Figures 2 and 4. It will be understood that the correction composition coats the outer face of the tape ribbon as it approaches the tip edge 6 from the ridge 11. Furthermore this ribbon face is also directed away from the surfaces of the ridge 12 so that there will be no tendency for the tape to stick to the tip 10 even if there are traces of correction composition remaining on the ribbon after it has passed around the tip edge.

On either side of the tip, adjacent the edge 6, are a pair of protruding guide wings 16 to assist in guiding the tape between the ridges 11, 12 and the edge 6. If required a pin 17 may be inserted to extend between the wings on one or both sides of the tip to provide a positive retention of the tape between the wings.

It will be appreciated that the geometry of the tip requires that the angle of inclination  $y$  (Fig. 4) of the ridge edges to the tip edge direction is substantially equal to half the sum of  $90^{\circ}$  and the angle of inclination  $x$  of the tape feed direction to the tip edge direction.

As the case 1 is elongated in the tape feed direction, the angle  $x$  is also the "writing angle" of the dispenser, i.e. the angle at which it is held in a downwardly and forwardly inclined orientation in use. A suitable "writing angle" would be in the range of  $45^{\circ}$  to  $75^{\circ}$ , preferably about  $60^{\circ}$ .

For laying down a strip of correction composition, the case of the dispenser may be held comfortably in the hand in essentially the same way as a conventional writing instrument would be gripped, that is mainly between the thumb and forefinger. The dispenser is held so that the tip edge 6 lies flat against the paper surface P, except that the tape 4 is interposed between the tip and the paper. The dispenser is then displaced across the paper in the lateral direction, normal to the tip edge 6, as indicated by the arrow in Figure 2. Under the pressure exerted through the tip, the correction composition adheres to the papers surface and the tip slides along the tape ribbon causing fresh tape to be drawn from the supply spool 2 and laid down immediately in front of the moving tip while ribbon over which the tip has passed is drawn back into the case 1 and is reeled up onto the take-up spool 3, having left the correction composition previously carried thereby on the paper. Thus, a continuous band of correction composition with a length corresponding to the distance travelled by the tip is laid down without demanding any specific dexterity on the part of the person using the tape dispenser.

Each of the two modified correction tape dispensers illustrated in Figures 6 and 7 and 8 and 9, respectively, is basically similar to the first embodiment and the same reference numerals have been used to denote corresponding parts. Each modified dispenser includes a case 1 housing tape supply and take-up spools 2 and 3, the spools being coupled by a slipping clutch mechanism and

the tape 4 consisting of a layer of correction composition coating one side of a carrier ribbon. Protruding from a forward end of the elongated case is the tip member 5 defining the edge 6 used to press the tape against the paper surface for transferring a strip of correction composition from the carrier ribbon onto the paper, a length of tape 4 extending between the supply and take-up spools being guided to pass around the tip edge. The tip member includes guide means for redirecting the tape so that the edge 6 is inclined in the feed direction in which the tape travels towards the tip member, and the correction tape dispenser has a "writing angle" of  $45^{\circ}$  to  $75^{\circ}$ , preferably about  $60^{\circ}$ , to the paper.

In the dispenser of Figures 6 and 7, the tip member is attached to and conveniently integral with a plastics carrier frame which supports the spools 2, 3. The member 5 includes a tip 10 with an edge portion and a guide portion which is inclined to the edge portion and is generally L-shaped in cross-section to define a shoulder 21 at which the guide and edge portions meet. Fixed to or integral with the guide portion is a tape guide peg 22, and defined by a ridge 12 is a rectilinear edge inclined to the tape feed direction. On either side of the tip, near the edge 6, are a pair of wing projections 16 spaced apart by a distance equal to the width of the tape. The tape 4 passes forwardly from the supply spool 2 to the peg 22 around which it passes so that the tape then extends towards the edge 6 in a direction essentially at  $90^{\circ}$  to that edge. The tape section between the peg 22 and the edge of shoulder 21 is twisted through  $90^{\circ}$  about its longitudinal axis. From the shoulder 21, the tape passes around the tip edge 6 in a plane substantially perpendicular to the tip edge, and eventually reaches the ridge 12 across which it rolls over onto the first side of the



tip member to pass on towards the take-up spool. The wing projections 16 serve to maintain the tape in correct alignment with the edge 6.

In the construction illustrated in Figures 8 and 9, the tip member 5 has a pair of opposed guide pegs 22, 23 on opposite sides thereof, and the supply and take-up spools 2,3 are shown mounted to face in opposite directions although this is not essential. The edge portion of the tip is largely similar to that of the dispenser of Figures 6 and 7, but has a more rounded or bulbous form opposite the edge 6. The tape guidance is essentially the same on both sides of the tip member with the tape being twisted through  $90^{\circ}$  in passing from the peg 22 to the edge 6 and being twisted through a further  $90^{\circ}$  between the edge 6 and the peg 23.

In use the modified dispensers are held and moved across the paper exactly as described above in relation to the embodiments of Figures 1 to 5. The modified tape guiding means have the advantage of reducing the area of contact between the tape and the tip member so that frictional resistance to tape advancement is diminished and smooth operation of the correction device thereby is enhanced. With a view to reducing friction still further the guide pegs could be equipped with or be replaced by rollers.

Figure 10 illustrates in more detail the tape retaining means associated with the tip edge and consisting of the wings 16 and pin 17 which together with the tip form an eye through which the tape passes. Figure 11 shows a modified construction in which a substantially closed eye is defined by opposed L-shaped projections 30 integral with the tip and between which a slot 31 is formed to enable the tape to be introduced laterally into the eye. Figure 12 shows another modification in which the L-shaped projections 30 overlap, but are displaced

along the tip to provide the slot 31 for insertion of the tape. In the construction of Figure 13, an eye for the tape is defined on each side of the tip by a sleeve 32 surrounding the tip. The sleeve could be integral with the tip or be formed as an extension on the dispenser body or case. Preferably, however, the sleeve is a separate collar which can be pushed over the tip end after the tape has been correctly positioned around the tip edge. In the further modification of Figure 14, the tip 10 has an I-shape cross section to locate and positively define the eyes with the collar. Finally, in Figure 15 the tip is equipped with extensions 33 to elongate the tip edge and reduce the chances of the tape becoming displaced over an edge extremity in use of the dispenser.

CLAIMS:-

1. A correction tape dispenser comprising a tip having an edge for pressing the tape against a surface, a portion of tape between supply and take-up spools being guided to extend around said edge, wherein the edge is inclined to the feed direction in which the tape is guided to the tip, and the tip includes guide means on either side of the edge for redirecting the tape so that the path of the tape around the edge between the guide means is in a plane substantially perpendicular to said edge and inclined to the feed direction.

2. A correction tape dispenser according to claim 1, wherein the tip guide means on at least one side of the edge comprises a linear edge around which the tape passes from one side to the other side thereof.

3. A correction tape dispenser according to claim 2, wherein the linear edges are provided on both sides and are defined by parallel ridges.

4. A correction tape dispenser according to claim 3, wherein the tape extends to the inner faces of the respective ridges from the supply and take-up spools, respectively.

5. A correction tape dispenser according to any one of claims 1 to 4, wherein tape positioning means are provided to determine a first fixed position from which the tape passes to the tip in the feed direction, and a second fixed position to which the tape passes after leaving the tip.

6. A correction tape dispenser according to claim 5 wherein the tip is provided by a unitary member and said tape positioning means are attached to said tip member.

7. A correction tape dispenser according to claim 1, wherein the guide means on at least one side of the tip comprises a guide element around which the tape passes to define a bend in the tape path.

8. A correction tape dispenser according to claim 7, wherein the guide element is arranged to maintain the tape at the bend substantially perpendicular to the tip edge.

9. A correction tape dispenser according to claim 8, wherein the tape is twisted longitudinally through substantially  $90^{\circ}$  between the guide element and the tip edge.

10. A correction tape dispenser according to claim 8 or 9, wherein the guide element defines an arcuate surface contacted by the tape and having an axis substantially perpendicular to a plane containing the tip edge and parallel to the feed direction.

11. A correction tape dispenser according to claim 8, 9 or 10, wherein the guide element comprises a lateral projection on a tip member supporting the tip edge.

12. A correction tape dispenser according to any one of claims 7 to 11, wherein guide elements are provided on both sides of the tip.

13. A correction tape dispenser according to any one of claims 1 to 12, wherein the supply and take-up spools

have rotational axes substantially perpendicular to a plane containing the tip edge and parallel to the tape feed direction.

14. A correction tape dispenser according to any one of claims 1 to 13, wherein the tip edge direction and the feed direction are at an angle in the range of about  $45^{\circ}$  to  $75^{\circ}$  to each other.

15. A correction tape dispenser according to any one of the preceding claims, wherein retaining means are provided adjacent at least one side of the tip edge for maintaining the tape in correct cooperation with said edge.

16. A correction tape dispenser according to claim 15, wherein the retaining means comprises a pair of projections between which the tape passes.

17. A correction tape dispenser according to claim 16, wherein an element extends between the projections to prevent the tape becoming disengaged therefrom.

18. A correction tape dispenser according to claim 15, wherein the tape retaining means is arranged to define with the tip a substantially closed eye through which the tape passes.

19. A correction tape dispenser according to claim 18, wherein the retaining means comprises a pair of oppositely directed L-shaped projections, a slot being formed between the projections to allow the tape to be inserted through the eye.

20. A correction tape dispenser according to claim 18, wherein the retaining means comprises a part surrounding the tip to form an eye on either side thereof.

21. A correction tape dispenser according to claim 20, wherein said retaining part is a collar engaged with a push fit over the tip edge.

22. A correction tape dispenser according to any one of claims 1 to 20, wherein the tip edge is provided with extension portions to reduce the chances of the tape becoming displaced over an end extremity of the tip edge.

23. A correction tape dispenser having a tip substantially as herein described with reference to the accompanying drawings.

24. A correction tape dispenser according to any one of claims 1 to 23, including a case enclosing the supply and take-up spools, the case being elongated substantially in the feed direction.

ABSTRACT

CORRECTION TAPE DISPENSER

In a correction tape dispenser, wherein a backing ribbon carrying a layer of correcting composition is fed from a supply spool (2) around the edge (6) of an applicator tip (10) used to press the tape against a paper surface (P) to transfer the layer of correcting composition onto the paper, and back to a take-up spool (3), a tape guide system (11,12; 22,23) is provided near the tip to redirect the tape, the tip edge (6) being at an angle to the feed direction so that the body of the tape dispenser may be held in a forwardly and downwardly inclined orientation similar to that in which a writing instrument is normally held.

**THIS PAGE BLANK (USPTO)**



Group	Condition 1	Condition 2	Condition 3	Condition 4
Control	95%	90%	95%	100%
MCI	90%	65%	60%	60%
AD	80%	75%	70%	60%



**THIS PAGE BLANK (USPTO)**

2/6




Fig. 2

**THIS PAGE BLANK (USPTO)**




Fig. 3




Fig. 5





Fig. 4

**THIS PAGE BLANK (USPTO)**


4/6



**THIS PAGE BLANK (USPTO)**



5/6



**THIS PAGE BLANK (USPTO)**

6/6




Fig. 10




Fig. 11




Fig. 12




Fig. 13




Fig. 14




Fig. 15

**THIS PAGE BLANK (USPTO)**

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☒ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☒ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**

**THIS PAGE BLANK (USPTO)**